



# EO Bearing Imp&Exp .co.,ltd

## SX011828 Cross Cylindrical Roller Bearing INA Structure



Bearing No. SX011828

SX011828 Bearing 2D drawings and 3D CAD models

|   |   |
|---|---|
| Size  | 140x175x18 mm                               |
| Bore Diameter                                     | 140 mm                                      |
| Outer Diameter                                    | 175 mm                                      |
| Width   | 18 mm                                       |
| $d_i$ - 140 mm / Tolerance: K6<br>+0,004 / -0,021 | 140 mm / Tolerance: K6<br>+0,004 / 0,021    |
| $D_a$ - 175 mm / Tolerance:<br>h6 -0,025          | 175 mm / Tolerance: h6<br>0,025             |
| H - 18 mm / Tolerance:<br>+/-0,12                 | 18 mm / Tolerance: +/-0,12                  |
| $D_i$   | 157,7 mm                                    |
| $D_M$   | 157 mm                                      |
| $d_a$   | 156,3 mm                                    |
| h - 18 mm / Tolerance: E8<br>-0,01                | 18 mm / Tolerance: E8 0,01                  |
| $r_{min}$   | 1,1 mm                                      |
| S   | 1,5 mm                                      |
| m   | 1,1 kg / Weight                             |
|   | 0,015 mm / Running<br>accuracy, radial      |
|   | 0,010 mm / Running<br>accuracy, axial       |
| $S_{r min}$                                       | 0,005 mm / Min. radial<br>bearing clearance |
| $S_{r max}$                                       | 0,020 mm / Max. radial<br>bearing clearance |
| $S_{k min}$                                       | 0,010 mm / Min. axial tilting<br>clearance  |



## EO Bearing Imp&Exp .co.,ltd

|                      |   |
|----------------------|---|
| $S_{k \max}$         | 0,04 mm / Max. axial tilting clearance                                  |
| $RLO_{\max}$         | 0,004 mm / Low clearance:<br>Radial clearance                           |
| $RLO_{\max}$         | 0,008 mm / Low clearance:<br>Preload                                    |
| $VSP_{\min}$         | 0,005 mm / Min. bearing preload   |
| $VSP_{\max}$         | 0,020 mm / Max. bearing preload   |
| $C_a$                | 63000 N / Dynamic load rating (axial)                                   |
| $C_{0a}$             | 240000 N / Static load rating (axial)                                   |
| $C_r$                | 45000 N / Dynamic load rating (radial) (for radial load only)           |
| $C_{0r}$             | 96000 N / Static load rating (radial) (for radial load only)            |
| $n_{G \text{ Oil}}$  | 975 1/min / Limiting speed for oil lubrication with normal clearance    |
| $n_{G \text{ Fett}}$ | 485 1/min / Limiting speed for grease lubrication with normal clearance |
| $n_{G \text{ Oil}}$  | 485 1/min / Limiting speed for oil lubrication with preload             |
| Category             | Ball Bearings   |
| Inventory            | 0.0   |
| Manufacturer Name    | SCHAEFFLER GROUP  |
| Minimum Buy Quantity | N/A   |
| Weight / Kilogram    | 1.432   |
| EAN                  | 4012802440621   |
| Product Group        | B00234  |